



PRODUCT DESCRIPTION

With solid Die-Cast Aluminum construction and powered by a range voltage input driver, Pathfinder is a high performance down light for commercial and residential installations. Choose from a variety of sizes, shapes that are sharply angled or smoothly sloping, and various photocell and motion sensor options. Also available with enabled switch to toggle between 5 light Color Temperature settings, this popular sconce has even more versatility. Choose from Black, Architectural Bronze, or Metallic Silver outdoor-rated powder coat finishes.

MEASUREMENTS

DIMENSION : 5" W x 3.25" H x 0.75" Ext
HANGING WEIGHT : 0.55 lb

LAMPING

INPUT VOLTAGE : 120-277V
LUMENS : 300 Rated (110 Del.)
BULB : 1 x 3W LED PCB Integrated , 3W Total
BULB INCLUDED : (Integrated)
DIMMABLE : Triac or ELV at 120V
CRI : 90 CRI
COLOR_TEMP : 2700-3000-4000K
LIGHTING_DIRECTION : Down

FINISHES OPTION

 Black (BK)
 White (WT)

MATERIAL

Aluminum, Plastic

RATINGS

cETLus
Wet Location



ADDITIONAL

INSTALL UP/DOWN: Down
RATED LIFE 50000 Hours
OPERATING TEMPERATURE:
-20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER)
253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER
101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com