

Project:	Type:	Prepared By:	Date:
-----------------	--------------	---------------------	--------------



UPC: 192552005951

Features and Benefits

- Replacement for conventional decorative lamps
- Filament LED construction gives a unique traditional look and feel for decorative and ambient applications
- Rated for use in enclosed and open fixtures in dry and damp locations
- Longer lifespan compared to legacy equivalents minimizes replacement and maintenance costs
- ENERGY STAR Compliant, UL Listed
- Smooth warm to dim transition between 2200K to 3000K color temperatures
- Uniform dimming down to 10% (See Dimmer Compatibility List)

Technical Specifications

Performance

Product Type:
A-Line

Input Wattage:
4.5W

Lumens:
450lm

Efficacy:
100lm/W

L70 Lifespan:
15,000-Hour LED lifespan based on IES LM-70 results

Wattage Equivalency:
40W Incandescent

Compliance

UL Listed:
Suitable for damp locations

Enclosed Fixtures:
Suitable for use in enclosed fixtures

LED Characteristics

Color Temperature:
2200/3000K

Color Accuracy (CRI):
>90 CRI

Beam Angle:
230°

Electrical

THD:
59.70%

Power Factor:
0.7

Dimmable:
Yes

Operating Temperature:
-20°C to 45°C (-4°F to 113°F)

Input Voltage:
120V

Operating Frequency:

60 Hz

Construction

Bulb Shape:
A19

Endcap Material:
Polycarbonate

Enclosure Material:

Plastic

Installation

Base Type:
E26 Edison

Other

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Technical Specifications (continued)

\

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	9.8	7.4	10
PALLET	1500	48	40	22.72

Dimension

