



Project:	Type:
Prepared By:	Date:


Driver Info		LED Info	
Type	Constant Current	Watts	12W
120V	0.10A	Color Temp	4000K (Neutral)
208V	N/A	Color Accuracy	85 CRI
240V	N/A	L70 Lifespan	100,000 Hours
277V	N/A	Lumens	1,229 lm
Input Watts	11.1W	Efficacy	110.7 lm/W

Technical Specifications			
Compliance UL Listed: Suitable for wet locations. Suitable for mounting within 4 ft of the ground.		Performance Lifespan: 100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations	
IESNA LM-79 & LM-80 Testing: RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.		Green Technology: Mercury and UV free. RoHS-compliant components.	
Trade Agreements Act Compliant: This product is a product of Cambodia and a "designated country" end product that complies with the Trade Agreements Act		Optical NEMA Type: NEMA Beam Spread 6H x 6V	
LED Characteristics LEDs: Multi-chip, high-output, long-life LEDs		Installation Mounting: Heavy-duty mounting arm with "O" ring seal and stainless steel screws	
Color Stability: LED color temperature is warrantied to shift no more than 200K in color temperature over a 5-year period		Other Warranty: RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty .	
Color Uniformity: RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.		Electrical Driver: Innovative integrated driver technology with 120V TRIAC and ELV dimming	
Construction Thermal Management: Superior heat sinking with external Air-Flow fins		THD: 11.2% at 120V	
Housing: Die-cast aluminum housing, lens frame and mounting plate			
Reflector: Semi-specular, vacuum-metalized polycarbonate			
Lens: Microprismatic diffusion lens for smooth and even light distribution			
Gaskets: High-temperature silicone gaskets			
Finish: Our environmentally friendly polyester powder coatings are formulated for high-durability and long-lasting color			

Technical Specifications (continued)

Power Factor:
99.1% at 120V

Dimensions



Features

- 12W LED equivalent to 75W BR30/halogen/wide flood
- Mount as an uplight or downlight on a RAB Mighty Post or junction box
- Microprismatic diffusion lens for smooth and even light distribution
- 100,000-hour LED Lifespan

Ordering Matrix

Family	Wattage	Color Temp	Finish	Other Options
BULLET	12	N	W	
12 = 12W Blank = 5000K Cool N = 4000K Neutral A = Bronze Blank = Standard Y = 3000K Warm B = Black VG = Verde Green W = White				