

Project:	Type:
Prepared By:	Date:

Technical Specifications

Compliance

Buy American Act Compliance:

This product complies with the Buy American Act

The Build America, Buy America Act (BABA):

Light poles meet The Build America, Buy America Act (BABA) (Pub. L. No. 117- 58, §§ 70901-52).

Construction

Pole Material:

Reinforced fiberglass

Maximum EPA Per Wind Zone:

- 90 mph: 9
- 100 mph: 6.7
- 110 mph: 5.0
- 120 mph: 3.7
- 130 mph: 2.8
- 140 mph: 2.7
- 150 mph: 2.2
- 160 mph: 1.9
- 170 mph: 1.5
- 180 mph: 1.3

Burial Height:

4 ft

Height:

15 ft

Shape:

Round Tapered

Finish:

All poles come with bronze finish and 3-layer of protection against UV degradation. The third layer is the thermally bonded outer coating.

Pole Drilling:

All poles HH covers and cable entry are factory drilled

Cable Entry:

Cable entry provided on the direct burial poles with a diameter of 2 1/4"

Hand Hole and Covers:

2 1/2" x 5" hand hole is standard for all the poles and are located at 18" above ground level. The hand hole covers are made of durable, weather resistant material.

Caps:

The plastic cap is pre-assembled to the pole before shipping

Integral Anti Rotation Flange:

Direct bury poles comes with an integral anti rotation flange

Other

2-Year Limited Warranty:

The RAB 2-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.


Accessories:

Poles are shipped with pole cap. The anchor bolt kit, base covers for round poles are sold separately BOLT4/7: Anchor bolt kit for round poles. BCK-CP-R: Round composite pole base cover.

Terms of Sale:

Pole Terms of Sale is available [online](#).

Dimensions



Features

- Complies with Buy America Act
- 2-Year, limited warranty

Ordering Matrix

Family	Shape	Burial Height	Height	Drilled/Welded Tenon
CD	TR	4	15	D
	TR = Round Tapered S = Square	4 = 4 ft 5 = 5 ft	15 = 15 ft 20 = 20 ft 25 = 25 ft	D = Drilled WT = Welded Tenon