

Project:

Type:

Prepared By:

Date:



UPC: 019813834832

### Features and Benefits

- Natural light detection
- On-off functionality
- Hold time: 1 minute, 5 hours, or 8 hours
- Standard 3.5mm AUX port connection
- Threshold levels at 20 lx /50 lx /100 lx /300 lx
- Suitable for use in enclosed luminaire
- Do not expose directly to water
- Use only one module per lamp

### Technical Specifications

#### Performance

**Product Type:**  
DAYLIGHT Sensor

**L70 Lifespan:**  
50,000 Hours

#### Electrical

**Input Voltage:**  
15VDC

**Max Input Current:**  
0.1A

**Max Output Current:**  
0.02A

**Lux Options:**  
20/50/100/300lux

**Hold Time Options:**  
1min/5hr/8hr

**Input Frequency:**  
5.8 GHz +/- 75MHz

**Output Voltage:**  
10VDC

**Operating Frequency:**  
5.8GHz

**Operating Current:**  
20mA

**Transmit Power:**  
1mW

#### Compliance

**California Energy Commission (CEC) Status:**  
Lawful for Sales in California

#### Other

**Warranty:**  
RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

## Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	100	9.8	9.8	8
PALLET	10000	49.2	40	45.5

## Dimension

