




PRODUCT DESCRIPTION

Channels of Black are fused in an erratic fashion concealing a LED light source that emits a soft and even illumination to the surface below. Light intensity is adjustable down to 10% to allow for multiple room scene settings.



MEASUREMENTS

DIMENSION : 21.25" L x 21.25" W x 8.5" H
MAX OAH : 128.5" OAH
CANOPY : 6.75" W x 1.75" H x 6.75" L
HANGING WEIGHT : 5.28 lb

LAMPING

INPUT VOLTAGE : 120V
LUMENS : 2,500 Rated (1,600 Del.)
BULB : 1 x 36W LED PCB Integrated , 36W Total
BULB INCLUDED : (Integrated)
DIMMABLE : ELV
CRI : 80+ CRI
COLOR_TEMP : 3000K

FINISHES OPTION

 Black

MATERIAL

Aluminum, Steel

RATINGS

cETLus
Dry Location



ADDITIONAL

ADJUSTABLE
SLOPE: 70
RATED LIFE 50000 Hours
OPERATING TEMPERATURE:
-20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Contemporary
Lighting™

WESTERN DISTRIBUTION CENTER (HEADQUARTER)
253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746
EASTERN DISTRIBUTION CENTER
4200 SHIRLEY DR. | ATLANTA, GA 30336
P. 626.956.4200 | F. 626.956.4225 | et2online.com