

3" Tunable White Koto™ IC Airtight Housing

120/277V AC/50-60Hz. Must be used with Tunable White Koto™ LED Light Engines (ELK19TWD Series).



Features

- IC Airtight for direct contact with insulation.
- 120/277V AC/50-60Hz universal input voltage
- Smooth, flicker-free dimming and CCT tuning
- Dimmable to 0.1%, dim to dark
- E35KT10 (1000 lm, 14W) 4" Height
- E35KT12 (1250 lm, 18.3W) 5½" Height
- Control Modules Ordered Separately
- Damp location rated and wet location rated for wet location trims

Specifications

Wattage	14W
Lumens	1000 lm
Voltage	120/277V AC
Dimmable	0-10V
Lamp Type	LED
Wet Location	Rated for wet location trims
Damp Location Rated	

Technical Details

Construction: Double Wall IC Rated for direct contact with insulation. For use in IC and Non-IC conditions. Up to 1100 lumens. Housing adjusts in frame to accommodate up to 1 1/2" ceiling thickness. Airtight housing with gasket to restrict airflow in accordance with ASTM E-283 air-tight requirements.

Installation: Designed for ceiling plenums where 2x6 joists or taller are used. High strength hanger bars can easily be nailed to joists. Suitable for T-grid and drop ceiling applications. See installation sheet for detailed information. For use with ELCO Tunable White Koto™ LED Light Engines (ELK19TWD Series)

Junction Box: Positioned to accommodate straight conduit runs. Two 3/4" knockouts, Seven 1/2" trade size conduit knockouts, One 3/8" knockout. Four Pry-out knockout slots for easy romex installation.

Hanger Bars: Pre Installed hanger bars with True Nail easy installation in regular lumber, engineered lumber, and Laminated Beams. Integral T-bar slots for easy installation in T-Bars. Spans up 24" and can be repositioned 90°. Score lines allow for tool-free hanger bar size reduction. Integral leveling flange allows for single-person installation while easily aligning the housings with the joists.


Electrical: Driver is rated for 120V and 277V input (120/277V). High Efficiency driver with a power factor > 0.95.

Driver Options:


- Standard: Integrated dual-channel 0-10V Dimming, no control module required
- elDoLED: Integrated dual channel 0-10V Dimming, no control module required
- Control Ready: For use with control module options, ethernet cables and connectors purchased separately
- Lutron: Integrated dual channel 0-10V Dimming, no control module required
- AmbienTech: Includes control module, compatible with AmbienTech ecosystem only

Dimmability: 0-10V dimming in one driver. 0-10V dimming down to 5% with a compatible dimmer. Can be specified with Lutron drivers for 0.1% and 1% dimming. For a full list of dimmers refer to the Dimmer Compatibility List.

E35KT10 Dimensions



E35KT12 Dimensions



Product Number

Item	Description	Lamp type	Lumens	Watts	Voltage	Dimming
E35KT10ICAD	IC Airtight Housing	LED	1000 lm	14W	120/277V AC	0-10V

Product Number Builder

Example: E35KT10ICAD

3" Tunable White Koto™ IC
Airtight Housing

E35KT

Lumens

101000 (14W)

121250 (18.3W)

IC Rated

ICAIC Airtight Housing

Driver

D

Dual 0-10V

ED

eldoLED

C

Control Ready

L

Lutron

A

AmbienTech

Compatible Products

For use with Dedicated 3" & 4" Koto Tunable White Housings



Control Modules Features

- Requires control ready housing
- Seamless device commissioning
- Rules setting and supervision
- Data gathering on usage, locations, users, time of day
- Automation based on users and sensors
- Firmware updates over the air
- Customizable and integration-ready APIs
- Control module required per housing

Wireless Control Modules for Tunable White Koto™



Technology Partner
SILVAIR  

ETW3SL

- iOS app and web portal interface options
- Energy usage monitoring
- Ecosystem with sensors, switches



WIZ     

ETW3WZ

- iOS app, Android app, and web portal interface options
- Predictive Maintenance
- Ecosystem with sensors and switches, lamps and luminaires



WISILICA   

ETW3WS

- iOS app, Android app, and web portal interface options
- Energy usage monitoring
- Predictive Maintenance
- Ecosystem with sensors, switches, gateways

Wired Control Protocol for Tunable White Koto™

**Wired control devices required*



ETW3DL

- DALI-2 DT8 certified
- Two-channel control of color temperature and intensity
- Commission and manage lighting fixtures via DALI2 DT8 certified controller



ETW310V

- 0-10V Control Module is compatible with industry standard 0-10V, 1-10V current sourcing or current sinking wired control devices. The Control Module provides for two-channel control of color temperature and intensity

Requires Control Ready Housing Option. One Control module required per housing


**Control Modules Order Separately*

Compatible Products

For use with Dedicated 3" Tunable White Koto™ IC LED Housings



Koto™ LED Module



Tunable White
Koto™ LED Module
ELK19

PRODUCT NUMBER BUILDER				
Koto™ LED Module	Color Temperature		Beam Angle	
ELK19				
	TWD	2700K - 5000K	(blank)	38° lens (Standard)
	T41D	1800K - 4000K	-S	18° lens
	T62D	2700K - 6500K	-N	25° lens
			-W	60° lens

ACCESSORIES



Lens

EP731C 18° Lens
EP732C 25° Lens
EP733C 38° Lens
EP734C 60° Lens

**EP732C, EP733C, EP734C Included*



Snoot

L50W White
L50B Black



Secondary Optics

L45 Hex Louver
L46 Linear Lens
L47 Spread Louver
L49 Frosted Lens
L51 Color Shifter

3" Pex™ Twist-On Trims



Deep Reflector

ELK3618

Finishes:

(W, BB, BZ, B, C, H)



Adjustable Gimbal

ELK3629

Finishes:

(W, BB, BZ, B, C, H)



Adj. Reflector Wall Wash

ELK3622

Finishes:

(W)



Adjustable Pinhole

ELK3627

Finishes:

(B, BB, BZ)




Adjustable Baffle

ELK3693

Finishes:

(W)




Sq. Deep Reflector

ELK3318

Finishes:

(W, BB, BZ, B, C, H)



Sq. Adjustable Gimbal

ELK3329

Finishes:

(W, BB, BZ, B, C, H)



Sq. Adjustable Pinhole

ELK3327

Finishes:

(B, BB, BZ)



Sq. Adjustable Baffle

ELK3393

Finishes:

(W)



Square Reflector

ELK3341

Finishes:

(W, B, BB, BZ)

*Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **B** - Black Reflector w/White Ring,
C - Chrome Reflector w/White Ring, **H** - Haze Reflector w/White Ring

Compatible Products

For use with Dedicated 3" Tunable White Koto™ IC LED Housings



3" Pex™ Trimless



Spackle Frame
EL3SFR



Adjustable Trimless Reflector
ELK315
Finishes:
(W, B, H)

3" Knife Edge Wood Ceiling Trim • For use with ELK315



Round Adaptor with Mounting Clips
EL3WCR
Finishes:
(W, B)




Adjustable Trimless Reflector
ELK315
Finishes:
(W, B, H)

3" Flush Mount Trim Adaptors • For use with ELK36 & ELK33 Trims




Round Flush Mount
EL3FMR



Square Flush Mount
EL3FMS

3" Accessories



Emergency Battery Backup



Fire Cover



Fire Enclosure



Mica Fire Tape

CAT NO.	SPECIFICATIONS	CAT NO.	SPECIFICATIONS	CAT NO.	SPECIFICATIONS	CAT NO.	SPECIFICATIONS
KEM-LD5	8W, 120/277V	FIRECVR	9 3/4" H x 17" O.D.	FIREENCL	20 3/8" L x 14 3/8" W	FIRETAPE	3/4" W x 16' L
* Requires access from above				FIREENCL-S	Shallow, 16" L x 14 3/8" W		