



Color: Black cord with clear filament style bulbs

Weight: 8.2 lbs

Project:	Type:
Prepared By:	Date:

Driver Info		LED Info	
Type	N/A	Watts	23W
120V	N/A	Color Temp	Tunable White 1800-5000K
208V	N/A	Color Accuracy	>80 CRI
240V	N/A	L70 Lifespan	15,000 Hours
277V	N/A	Lumens	610 lm
Input Watts	23W	Efficacy	27

Technical Specifications

Lightcloud

Lightcloud Blue:

Lightcloud Blue is a Bluetooth® Mesh lighting control system designed for fast setup and flexibility. Install quickly with no gateways, hubs, or additional control wiring. Start with a single device and easily scale to control entire buildings. Learn more at rablighting.com/lcb.

DLC system - N1XMLOEATBA (Interior);
NHCZ2BIA17L (Exterior)

Gateway Required:

No

Communication Protocol:

Bluetooth Mesh

SmartShift:

SmartShift Ready to easily configure automated lighting profiles to automatically adjust brightness and color temperature for circadian and aesthetic needs.

Light Shows:

No, this product is not compatible with dynamic color changing Light Shows. Contact RAB for more information.

Range:

Indoor: Up to 60 feet between standard building materials. Building materials such as brick, concrete, and steel construction may require additional Lightcloud Blue devices to extend around an obstruction; Up to 200 feet clear line of sight.

Outdoor: Up to 200 feet clear line of sight; Up to 120 feet around corners

Spacing Criteria:

Lightcloud Blue devices should be placed within the specified range to communicate within the Bluetooth Mesh network. Building materials such as brick, concrete, and steel construction or heavy vegetation, bushes or trees may require additional Lightcloud Blue devices to extend around an obstruction.

Sensor Settings

Remote Control Accessory:

Yes, with additional devices, sold separately. Small projects use Nano to link with Amazon Alexa or Google Home for wireless control using those apps. Larger projects require one XDIM Bridge per Area plus a Gateway for full remote access via Lightcloud web portal or mobile app.

Performance

Product Type:

Decorative String Light, Smart

Description:

Flexible 50 ft string lights with filament-style bulbs, linkable to 150 ft, tunable white using Lightcloud Blue

Input Wattage:

23W

Lumens (Nominal):

610lm

Efficacy:

27lm/W

L70 Lifespan:

15,000-Hour LED lifespan based on IES LM-70 results

Electrical

Driver:

Constant Voltage, Class 2 120-277V 50/60; 120V: 210mA; 208V: 123mA; 240V: 107mA; 277V: 92mA

THD:

<20%

Power Factor:

0.9

Technical Specifications (continued)**Dimmable:**

Yes, using Lightcloud Blue. This product will not operate properly when connected to a standard (incandescent) dimmer or dimming control.

Input Voltage:

120-277V

Construction**Operating Temperature:**

-4°F(-20°C) to 104°F (40°C)

Length:

50 ft

Bulbs per String:

24

Max Run Length:

150 ft

Shape:

S14

Finish:

Black cord with clear filament style bulbs

Enclosure Material:

Glass

Lens Finish:

Clear

LED Characteristics**Beam Angle:**

120°

Color Temperature:

Default: 3000K

Adjustable using the Lightcloud Blue mobile app

Tunable White 1800 - 3000K

Color Tuning:

No

Color Accuracy (CRI):

>80 CRI

Natural Spectrum:

No

R9 Value:

High color performance with R9 greater than 0

Color Consistency:

<3-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

Installation**Mounting:**

Plugs into a standard 15A 125V duplex receptacle

Base Type:

NEMA 1-15, 2-prong plug

Replaceable Bulbs:

Individual bulbs are not replaceable

Compliance**Environment:**

Suitable for use indoors and outdoors in dry, damp, or wet environments.

Certification Model Number:

GLW/LCB

California Title 24 JA8 Compliant:

No

California Energy Commission (CEC) Status:

Lawful for Sales in California

RoHS:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15 of the FCC Rules

Other**Compatible Accessories:**

EXTCBL-GLW/LCB


25 ft. Extension cable

Compatible with other Lightcloud Blue Devices for scalable control.

3-Year, No-Compromise Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Dimensions



Features

- 50 ft Decorative string with 24 S14 filament bulbs
- Linkable up to 150 ft maximum run
- Bluetooth mesh control on Lightcloud Blue models
- Simple plug-and-play installation, no wiring required
- Ideal for patios, restaurants, events, and retail spaces

Ordering Matrix

Family	Length	CRI/Color Temp	Driver	Finish	Controls
GLW					/LCB
	Blank = 50 ft	Blank = 80 CRI, Tunable White	Blank = 120-277V	Blank = Black cord w/glass bulbs	/LCB = Lightcloud Blue /RGB = Lightcloud Blue, 16+ million colors