

Project:

Type:

Prepared By:

Date:



UPC: 019813908151

Features and Benefits

- Energy efficient replacement for incandescent and halogen Small diameter reflectors
- Constructed from durable materials which lowers risk of breakage
- Rated for use in enclosed and open fixtures in dry or damp locations
- Single optic and full face lens for precise beam angle control
- Longer lifespan compared to legacy equivalents minimizes replacement and maintenance costs
- ENERGY STAR Compliant, UL Listed

Technical Specifications

Performance

Product Type:
Small-Reflector

Input Wattage:
4.5W

Lumens:
350lm

Efficacy:
77lm/W

L70 Lifespan:
25,000-Hour LED lifespan based on IES LM-70 results

Wattage Equivalency:
50

LED Characteristics
Color Accuracy (CRI):
80

Color Temperature:
3000K

Beam Angle:
35°

Electrical
Power Factor:
>0.7

Dimmable:
Yes, down to 10%

Input Voltage:
120V

Operating Frequency:
60 Hz

Operating Temperature:
-20°C to 45°C

Construction
Bulb Shape:
PAR16

Enclosure Material:
Plastic

Housing Finish:
White

Installation
Base Type:
GU10

Other
Technology EQ:
Halogen

Warranty:
RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Compliance
UL Listed:
Yes

Environment:
Damp / Enclosed

Technical Specifications (continued)

Rohs:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15B of the FCC Rules

\ _____

Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity
10	1

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	10	0	0	0
PALLET	3120	0	0	0

Dimension

