

Project:	Type:	Prepared By:	Date:
-----------------	--------------	---------------------	--------------



Features and Benefits

- Energy efficient replacement for incandescent and halogen Small diameter reflectors
- Constructed from durable materials which lowers risk of breakage
- Rated for use in enclosed and open fixtures in dry or damp locations
- Single optic and full face lens for precise beam angle control
- Longer lifespan compared to legacy equivalents minimizes replacement and maintenance costs
- ENERGY STAR Compliant, UL Listed

Technical Specifications		
Performance	Beam Angle:	Housing Finish:
Product Type: Small-Reflector	35°	White
Input Wattage: 4.5W	Electrical	Installation
Lumens: 350lm	Power Factor: >0.7	Base Type: GU10
Efficacy: 77lm/W	Dimmable: Yes, down to 10%	Other
L70 Lifespan: 25,000-Hour LED lifespan based on IES LM-70 results	Input Voltage: 120V	Technology EQ: Halogen
Wattage Equivalency: 50	Operating Frequency: 60 Hz	Warranty: RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty .
LED Characteristics	Construction	Compliance
Color Accuracy (CRI): 80	Bulb Shape: PAR16	UL Listed: Yes
Color Temperature: 5000K	Enclosure Material: Plastic	Environment: Damp / Enclosed

Technical Specifications (continued)

Rohs:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15B of the FCC Rules

\ _____

Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity
10	1

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	10	0	0	0
PALLET	3120	0	0	0

Dimension

