

Project:	Type:	Prepared By:	Date:
-----------------	--------------	---------------------	--------------



Features and Benefits

- Replacement for traditional Metal Halide or High Pressure Sodium HID Lamps
- Integral Driver enables lamp to be wired directly to line voltage without need for an external driver or ballast
- Rated for use in enclosed and open fixtures in dry or damp locations
- Lightweight design
- Omnidirectional light output
- 25,000 hour Lifespan
- Environmentally friendly, no mercury used
- UL Recognized
- Non-Dimmable
- 3 Year Limited Warranty

Technical Specifications		
<p>Performance</p> <p>Product Type: HID Replacement</p> <p>Input Wattage: 26W</p> <p>Lumens: 3,450lm</p> <p>L70 Lifespan: 25,000-Hour LED lifespan based on IES LM-70 results</p> <p>Wattage Equivalency: 50W</p> <p>LED Characteristics</p> <p>Color Accuracy (CRI): 80</p> <p>Color Temperature: 5000K</p> <p>Beam Angle: 180°</p>	<p>Electrical</p> <p>Power Factor: >0.9</p> <p>Dimmable: Non-Dim</p> <p>Input Voltage: 120-277V AC</p> <p>Operating Frequency: 60 Hz</p> <p>Operating Temperature: -20°C to 40°C</p> <p>Construction</p> <p>Bulb Shape: T-Shape</p> <p>Enclosure Material: Plastic</p> <p>Housing Finish: White</p>	<p>Installation</p> <p>Base Type: E26 Edison</p> <p>Installation Method: UL Type B, Ballast Bypass</p> <p>Burning Position: Universal</p> <p>Other</p> <p>Technology EQ: Metal Halide or High Pressure Sodium</p> <p>3 Yr Limited Warranty: The RAB 3-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty</p> <p>Compliance</p> <p>Listings: UL Recognized</p> <p>Environment: Damp / Enclosed</p>

Technical Specifications (continued)

IP Rating:
IP64

RoHS:
Mercury and UV free. RoHS-compliant components.

FCC:
Complies with Part 15B of the FCC Rules

\ _____

Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity
20	1

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	0	0	0
PALLET	360	0	0	0

Dimension

