

UPC: 192552015691

Weight: 0.1 lbs

<b>Project:</b>	<b>Type:</b>
<b>Prepared By:</b>	<b>Date:</b>

Driver Info		LED Info	
Type	Constant Current	Watts	6W
120V	0.07A	Color Temp	2200K-4500K
208V	N/A	Color Accuracy	90 CRI
240V	N/A	L70 Lifespan	15,000 Hours
277V	N/A	Lumens	800 lm
Input Watts	6W	Efficacy	133

### Technical Specifications

#### Performance

**Product Type:**

Bluetooth-Enabled Filaments

**Input Wattage:**

6W

**Lumens:**

800lm

**Efficacy:**

133lm/W

**Lifespan:**

15,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

#### LED Characteristics

**Color Accuracy (CRI):**

>90 CRI

**Beam Angle:**

360°

**Color Temperature:**

2200K-4500K

#### Electrical

**Power Factor:**

0.7

**Dimming:**

Dimmable via Lightcloud Blue mobile app

**Flicker:**

<30%

**Operating Temperature:**

-20°C to 45°C (-4°F to 113°F)

**Input Voltage:**

120V

**Operating Frequency:**

60Hz

#### Construction

**Material:**

Glass

**Bulb Shape:**

ST19

#### Installation

**Base Type:**

E26, Medium Screw Base

#### Compliance

**UL Listed:**

Suitable for wet locations

**Fixture Rating:**

Enclosed

**Other**


**Warranty:**

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

**Case and Pallet Dimensions**

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	8	11.38	5.79	6
PALLET	768	46.3	35.91	26.4

**Dimension**



**Features**

- Direct Connect to the Lightcloud Blue mobile app via Bluetooth, no Gateway or Hub required
- Use mobile device to configure features for On/Off Control, Dim Level, Color Temperature, Schedules, Scenes, SmartShift and more.
- Tunable White 2200-4500K with smooth transition between color temperatures
- Circadian SmartShift Capable to sync with local sunrise/sunset
- Suitable for open or enclosed fixtures in dry, damp, or wet environments.
- Title 20 Compliant, ENERGY STAR® compliant, UL Listed

**Ordering Matrix**

Family	Bulb	Wattage	Base Type	CRI/Color Temp	Type	Finish	SmartShift
LCB	ST19	6	E26	9TW	F	C	SS
	A19 = A19 G25 = G25 ST19 = ST19 B11 = B11	5 = 5W 6 = 6W	E26 = E26 Base	9TW = 90 CRI, Tunable White	F = Filament	C = Clear	SS = SmartShift