



UPC: 192552002042

Color: Black

Weight: 0.0 lbs

Project:

Type:

Prepared By:

Date:

## Technical Specifications

### Performance

**Product Type:**

Wired Sensor

**Description:**

Microwave motion detector and daylight sensor that can switch and dim both local and remote circuits. For use with compatible Lightcloud Blue Controllers and fixtures.

### Lightcloud

**Lightcloud Blue:**

Lightcloud Blue is a Bluetooth Mesh wireless lighting control system that allows you to control RAB's various compatible devices. With RAB's patented Rapid Provisioning technology, devices can be quickly and easily commissioned for residential and large commercial applications using the Lightcloud Blue mobile app. Each device in a system can communicate with any other device, eliminating the need for a Gateway or Hub and maximizing the control system's reach.

DLC system - N1XMLOEATBA (Interior);  
NHCZ2BIA17L (Exterior)

Learn more at [www.lightcloud.com](http://www.lightcloud.com).

**Gateway Required:**

No

**Communication Protocol:**

Bluetooth Mesh

**Range:**

Up to 60 ft between standard building materials. Up to 200 ft clear line of sight.

**Spacing Criteria:**

Lightcloud Blue devices should be placed within the specified range to communicate within the Bluetooth Mesh network.

### Electrical

**Connection Type:**

RJ09

**Input Voltage:**

5V

**Operating Frequency:**

DC

**Low Voltage:**

Only connect to compatible Lightcloud Blue Controllers

**Operating Temperature:**

-4°F to 113°F (-20°C to 45°C)

**Max Mounting Height:**

8 ft to 12 ft

**Detection Range:**

20 ft diameter at 9 ft mounting height

**Cord Length:**

12 in

### Sensor Settings

**Default Setting:**

Uncommissioned State:  
Sensor Status: Enabled  
Motion Sensitivity: High  
Brightness when triggered: 100%  
Hold time: 1 minute  
Standby to dim: 20%  
Standby time: 1 minute  
When vacant: Off

Commissioned State:

Sensor Status: Disabled, once enabled the following default are set.  
Motion Sensitivity: High  
Brightness when triggered: Last on status  
Hold time: 20 minutes  
When vacant: Off

**Sensing Type:**

Occupancy or Vacancy

**Occupied Actions:**

On or On at a Dim Level

**Vacant Options:**

Off or On at a Dim Level

**Occupancy Timeout:**

1 minute to 240 minutes

**Technical Specifications (continued)****Daylight Sensing:**

The sensor will determine to trigger the light(s) on or not based on the daylight threshold level set in the Lightcloud Blue mobile app.

**Daylight Threshold:**

150 lux to 1500 lux

**Construction****Finish:**

Black

**Lens Finish:**

White

**Shape:**

Rectangle

**Enclosure Material:**

Plastic

**Compliance****Listings:**

UL Listed

**Environment:**

Suitable for damp environments in indoor applications

**DLC NLC Listed:**

This product is on the Design Lights Consortium (DLC) Network Lighting Controls (NLC) Qualified Products List and is eligible for rebates from DLC Member Utilities.

DLC system - N1XMLOEATBA (Interior);

NHCZ2BIA17L (Exterior)

**Certification Model Number:**

LCLCSENSE/M/EG/A

**T20 Compliant:**

Not applicable

**California Title 24 JA8 Compliant:**

Not applicable

**California Energy Commission (CEC) Status:**

Lawful for Sales in California

**RoHS:**

Mercury and UV free. RoHS-compliant components.

**FCC:**

Complies with Part 15B of the FCC Rules

**Other****Compatible Products:**

Must be connected to the LCBLUECONTROL/W on the:

EZPAN Family

EZPANFA Family

**Warranty:**

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

