

Project:	Type:	Prepared By:	Date:
-----------------	--------------	---------------------	--------------



Features and Benefits

- Energy efficient replacement for incandescent and halogen Small diameter reflectors
- Constructed from durable materials which lowers risk of breakage
- Rated for use in enclosed and open fixtures in dry or damp locations
- Single optic and full face lens for precise beam angle control
- Longer lifespan compared to legacy equivalents minimizes replacement and maintenance costs
- ENERGY STAR Compliant, UL Listed

Technical Specifications		
Performance	Beam Angle:	Housing Finish:
Product Type: Small-Reflector	35°	White
Input Wattage: 7.5W	Electrical	Installation
Lumens: 570lm	Power Factor: >0.9	Base Type: GU5.3
Efficacy: 76lm/W	Dimmable: Yes, down to 10%	Optical
L70 Lifespan: 25,000-Hour LED lifespan based on IES LM-70 results	Input Voltage: 12V	MBCP: 1315
Wattage Equivalency: 50	Operating Frequency: 60 Hz	Other
LED Characteristics	Operating Temperature: -20°C to 45°C	Technology EQ: Halogen
Color Accuracy (CRI): 80	Construction	Warranty (Years): 3 years
Color Temperature: 3000K	Bulb Shape: MR16	Compliance
	Enclosure Material: Aluminum	UL Listed: Yes
		Environment: Damp / Enclosed
		Rohs: Mercury and UV free. RoHS-compliant components.

Technical Specifications (continued)

FCC:

Complies with Part 15B of the FCC Rules

\ _____

Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity
8	1

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	0	0	0
PALLET	4536	0	0	0

Dimension

