

<b>Project:</b>	<b>Type:</b>	<b>Prepared By:</b>	<b>Date:</b>
-----------------	--------------	---------------------	--------------



UPC: 192552005562

### Features and Benefits

- Replacement for high-output incandescent/halogen or ceramic metal halide
- Adjustable CCT to choose from 3000/4000/5000K
- Rated for use in enclosed fixtures in dry, damp, or wet locations
- 90+CRI provides high quality color rendering
- Shatterproof enclosure for rugged applications

## Technical Specifications

### Performance

**Product Type:**  
PAR

**Input Wattage:**  
19W

**Lumens:**  
1,800lm

**Efficacy:**  
163.6lm/W

**L70 Lifespan:**  
15,000-Hour LED lifespan based on IES LM-70 results

**Wattage Equivalency:**  
150W Halogen

### Compliance

**Enclosed Fixtures:**  
Suitable for use in enclosed fixtures

### LED Characteristics

**Color Temperature:**  
3000/4000/5000K

**Color Accuracy (CRI):**  
90 CRI

**Beam Angle:**  
40°

### Electrical

**THD:**  
<20%

**Power Factor:**  
0.9

**Dimmable:**  
Yes, dimmable down to 10% on compatible TRIAC/ELV dimming systems.

**Operating Temperature:**  
-20°C to 45°C (-4°F to 113°F)

**Input Voltage:**  
120V

**Operating Frequency:**  
60 Hz

### Construction

**Bulb Shape:**  
PAR38

**Endcap Material:**  
Aluminum

**Enclosure Material:**  
Plastic

### Installation

**Base Type:**  
E26 Edison

### Other

**Warranty:**  
RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

## Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	24	20.3	15.4	20
PALLET	432	47.24	41.34	37.01

## Dimension

