

Project:	Type:	Prepared By:	Date:
-----------------	--------------	---------------------	--------------



Features and Benefits

- Motion detection
- On-off functionality
- Slotted detection pattern
- Standby level options: off, 20% dim, 40% dim, or 60% dim
- Hold time options for motion detection: 30 seconds, 90 seconds, 5 minutes, 10 minutes
- Standard 3.5mm AUX port connection
- Do not use with enclosed metal luminaire
- IP20, don't expose directly to water
- Daylight Photocell built in with default threshold of 300 lx

Technical Specifications

Performance

Product Type:
PIR Sensor

Electrical

Operating Temperature:
-20°C to 60°C

Input Voltage:
15VDC

Max Input Current:
0.1A

Max Output Current:
0.02A

Detection Angle:
120 degrees

Max Mounting Height:
19.7 ft

Detection Radius:
13.12 ft

Standby Dim Levels:
0/20%/40%/60%

Input Frequency:
5.8 GHz +/- 75MHz

Input Current @ 120V:
Max 0.1mA @15V

Output Voltage:
10VDC

Operating Frequency:
5.8GHz

Operating Current:
20mA

Transmit Power:
1mW

Construction

For Use Outdoors in Open Fixtures:
No

Compliance

UL Listed:
Yes

California Energy Commission (CEC) Status:
Lawful for Sales in California

Other

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	100	9.8	9.8	8
PALLET	6400	45.1	39.4	39.4

Dimension

