



## PROLIGHTING LED Area Light

The PROLIGHTING LED area lights are an excellent choice to provide your parking lot or other large exterior area application with long lasting, energy efficient LED illumination. These fixtures are wattage selectable, allowing the user to choose between four different wattage and lumen output levels to best suit their application.

Each fixture is built with a 3-pin NEMA socket base with shorting cap for easy installation of a photocell (sold separately). Combine with your choice of slipfitter or direct mount brackets (sold separately). Being DLC Premium rated, these fixtures allow for even more savings when taking advantage of local energy utility rebates.

### FEATURES

- 120-277V operation
- Wattage selectable:
  - PL-SB02-150L-50K-T3-BR
    - 80W / 10,800 lumens
    - 100W / 13,500 lumens
    - 120W / 16,200 lumens
    - 150W / 20,250 lumens
  - PL-SB02-300L-50K-T3-BR
    - 180W / 24,300 lumens
    - 200W / 27,000 lumens
    - 240W / 32,400 lumens
    - 300W / 40,500 lumens
- Type III medium narrow beam angle
- Integrated 3-pin NEMA socket base and shorting cap
- Direct mount bracket and slipfitter mount brackets available (sold separately)
- Polycarbonate lens
- IP65 wet location rated
- 10kV surge protection
- DLC 5.1 Premium
- Operating temperature: -22° to 113° F
- 50,000 hour rated
- 5 year warranty



Model Number	PL-SB02-150L-50K-T3-BR	PL-SB02-300L-50K-T3-BR
Input Power	150 Watt	300 Watt
Lumens	20,250	40,500
Lumens Per Watt	135 lm/W	
Input Voltage	120-277V	
Dimmable	0-10V	
Color Temperature	5000K	
Color	Bronze	
Rated Hours	50,000	
Beam Angle	Type III - Medium Narrow	
Min Operating Temp	-22° F	
CRI	70+	
DLC Listed	Premium	
DLC ID	PIUMNNAJ	P7RWUHTQ
Special Features	Wattage/Lumen Selectable, IP65 Rated, Surge Protection	
Warranty	5 Years	

## MOUNTING OPTIONS



Slipfitter



Direct

## ACCESSORIES



Photocontrol