


DIMENSIONS:

2.95" DAIMETER X 5/8" H (1/16" When Recessed)



PL12-MCT5-WH
PL12-MCT5-BK
PL12-MCT5-BN

3" ROUND SLIM PUCK LIGHT

Ideal for under cabinet, display cases or in low profile areas.

ELECTRICAL SPECIFICATIONS:

- Working Voltage: 12VDC
- Wattage: 4W
- Efficacy: 62LM/W

HOUSING SPECIFICATIONS:

- PC Housing with white/black/ brushed-Nickel finish
- 3.3 ft. cord with male socket
- Mounting: Recessed
- Screwless Trim

LIGHTING SPECIFICATIONS:

- Total lumens: 250LM
- color temperature: 2700K/3000K/3500K/4000K/5000K (MCT5)
- Beam Angle: 120°

CERTIFICATIONS:



WARRANTY: 3 years

MODEL	WATTS	VOLTAGE	LUMENS	COLOR TEMP
PL12-MCT5-WH	4W	12VDC	250LM	MCT5
PL12-MCT5-BK	4W	12VDC	250LM	MCT5
PL12-MCT5-BN	4W	12VDC	250LM	MCT5

OPTIONAL ACCESSORIES:



MODEL	DESCRIPTION
PL12-SPLIT3-WH	3-Hole mini splitter with female socket & 40" cord, white
PL12-SPLIT3-BK	3-Hole mini splitter with female socket & 40" cord, Black
PL12-SPLIT6-WH	6-Hole mini splitter with female socket & 40" cord, white
PL12-SPLIT6-BK	6-Hole mini splitter with female socket & 40" cord, Black
PL12-SPLIT10-WH	10-Hole mini splitter with female socket & 40" cord, white
PL12-SPLIT10-BK	10-Hole mini splitter with female socket & 40" cord, Black
PL12-PF-WH	6" Power feed cord, White
PL12-PF-BK	6" Power feed cord, Black
PL12-PIDR-12W-WH	12W Plug-in driver with switch, white
PL12-PIDR-12W-BK	2W Plug-in driver with switch, Black
PL12-PIDR-24W-WH	24W Plug-in driver with switch, white
PL12-PIDR-24W-BK	24W Plug-in driver with switch, Black
PL12-ILDMR-WH	In-Line dimming control, White
PL12-ILDMR-BK	In-Line dimming control, Black
PL12-HWDR-25W-D	Dimmable driver, 100-240V

