

| | | | |
|-----------------|--------------|---------------------|--------------|
| Project: | Type: | Prepared By: | Date: |
|-----------------|--------------|---------------------|--------------|



Features and Benefits

- Omni directional light distribution
- Suitable for horizontal or vertical installations
- Replaces 26W/32W G24d & G24q
- Plug and Play on existing Magnetic CFL ballasts or can be wired directly to line voltage without need for an external driver or ballast
- Compatible with G24d / GX24d & G24q / GX24q installations
- 50,000 hour Lifespan
- Environmentally friendly, no mercury used
- UL Listed, UL Classified
- Rated for use in enclosed and open fixtures in dry or damp locations
- Non-Dimmable
- 5 Year No Compromise Warranty

| Technical Specifications | | |
|--|---|---|
| Performance | Beam Angle: | Enclosure Material: |
| Product Type: Compact | 360° | Polycarbonate |
| Input Wattage: 9W | Electrical | Housing Finish: White |
| Lumens: 1,250lm | THD: 20% | Lens Finish: Frosted |
| Efficacy: 139lm/W | Power Factor: >0.9 | Installation |
| L70 Lifespan: 50,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations | Dimmable: Non-Dim | Base Type: 2-Pin G24d |
| Wattage Equivalency: 26W/32W G24d & G24q | Input Voltage: 120-277 Type B (Type A dependent on ballast) | Installation Method: UL Type A with Magnetic Ballasts & UL Type B (Dual Mode) |
| LED Characteristics | Operating Frequency: 50/60Hz | Burning Position: Universal |
| Color Accuracy (CRI): 80 | Operating Temperature: -20°C to 45°C (-4°F to 113°F) | Other |
| Color Temperature: 3500K | Construction | Technology EQ: CFL |
| | Bulb Shape: PLC-O | |

Technical Specifications (continued)

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Compliance

Listings:

UL Listed, UL Classified

Environment:

Damp / Enclosed

RoHS:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15B of the FCC Rules

Certification Model Number:

T10196(PLC-9-O-835-HYB)

\


Minimum Compartment Size

| Length x Width x Height [in] | Lamp Quantity |
|------------------------------|---------------|
| 7 | 1 |

Case and Pallet Dimensions

| | QTY | LENGTH (in) | WIDTH (in) | HEIGHT (in) |
|--------|-----|-------------|------------|-------------|
| CASE | 12 | 0 | 0 | 0 |
| PALLET | 674 | 0 | 0 | 0 |

Dimension



Light Distribution

