

Project: _____ Type: _____ Prepared By: _____ Date: _____



Features and Benefits

- 4 color temperatures in 1 SKU (2700/3000/3500/4000K)
- Bypass versions replace 7W-13W CFL lamps with 2G7 & 2GX7 bases
- Ballast Bypass-Install directly to line voltage
- 5-Year, No-Compromise Warranty

| Technical Specifications | | |
|---|---|--|
| <p>Performance</p> <p>Product Type: PLS Bypass</p> <p>Description: PLS (Short) 2-Pin & 4-Pin compact fluorescent replacements with CCT-Adjustability</p> <p>Wattage Equivalency: 7-9W CFL</p> <p>Input Wattage: 3.5W</p> <p>Nominal Lumens: 360/370/380/400</p> <p>Efficacy: 113.7/114.6/127.0/123.8</p> <p>L70 Lifespan: 50,000-Hour LED lifespan based on IES LM-70 results</p> | <p>Electrical</p> <p>Driver: Constant Current; 120-277V; 50/60 Hz 120V: 30mA, 208V: 19mA, 240V: 16mA, 277V: 14mA</p> <p>THD: <20%</p> <p>Power Factor: 0.9</p> <p>Dimmable: No</p> <p>Input Voltage: 120-277V</p> <p>Operating Frequency: 50/60Hz</p> <p>Operating Temperature: -4°F to 113°F (-20°C to 45°C)</p> <p>Flicker: 50%</p> | <p>LED Characteristics</p> <p>Beam Angle: 120°</p> <p>Color Temperature: Field adjustable via dip switch 2700/3000/3500/4000K</p> <p>Color Accuracy (CRI): >80 CRI</p> <p>R9 Value: High color performance with R9 greater than 0</p> <p>Color Consistency: <7-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color</p> <p>Color Stability: LED color temperature is warrantied to shift no more than 200K in color temperature over a 5-year period</p> <p>Color Uniformity: RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.</p> |

Technical Specifications (continued)

Installation

Installation Method:

UL Type B, Ballast Bypass

Installation Orientation:

Horizontal

Base Type:

2G7

Construction

Shape:

PLS

Finish:

White

Endcap Material:

Copper

Enclosure Material:

Polycarbonate

Lens Finish:

Frosted

Compliance

Environment:

Suitable for use indoors in dry and damp environments.

Fixture Rating:

Suitable for use in enclosed fixtures.
Suitable for use in open fixtures.

DLC Listed:

No

Certification Model Number:

T20097(PLS-3.5-H-8FA-BYP-2G7)

California Title 20 Compliant:

No

California Title 24 JA8 Compliant:

No

California Energy Commission (CEC) Status:

Not Lawful for Sales in California

NSF Listed:

Meets NSF/ANSI standards for use in Food Zone (non-contact), Splash, and Non-Food Zones. Tube guard required in open fixtures.

IESNA LM-79 & LM-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

RoHS:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15 of the FCC Rules

Other

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Case and Pallet Dimensions

| | QTY | LENGTH (in) | WIDTH (in) | HEIGHT (in) |
|---------------|-----|-------------|------------|-------------|
| CASE | 12 | 6.02 | 5.71 | 3.39 |
| PALLET | 8 | 47.24 | 39.37 | 51.18 |

Dimension

