

Project:	Type:	Prepared By:	Date:
-----------------	--------------	---------------------	--------------



Features and Benefits

- 4 color temperatures in 1 SKU (2700/3000/3500/4000K)
- Omnidirectional light distribution, suitable for horizontal or vertical installations
- Compatible with G24d / GX24d & G24q / GX24q installations
- 5-Year, No-Compromise Warranty

Technical Specifications		
<p>Performance</p> <p>Product Type: PLT Bypass</p> <p>Description: PLC & PLT Omnidirectional Lamps. 4-Pin & 2-Pin compact fluorescent replacements with CCT-Adjustability</p> <p>Wattage Equivalency: 32W CFL</p> <p>Input Wattage: 15W</p> <p>Nominal Lumens: 2000/2100/2200/2200</p> <p>Efficacy: 143.05-151.87-151.93-157.16</p> <p>L70 Lifespan: 50,000-Hour LED lifespan based on IES LM-70 results</p>	<p>Electrical</p> <p>Driver: Constant Current; 120-277V; 50/60 Hz 120V: 135mA, 208V: 80mA, 240V: 69mA, 277V: 60mA</p> <p>THD: <20%</p> <p>Power Factor: 0.9</p> <p>Dimmable: No</p> <p>Input Voltage: 120-277V</p> <p>Operating Frequency: 50/60Hz</p> <p>Operating Temperature: -4°F to 113°F (-20°C to 45°C)</p> <p>Flicker: 50%</p>	<p>Color Temperature: Field Adjustable via dip switch 3000/3500/4000/5000K</p> <p>LED Characteristics</p> <p>Beam Angle: 360°</p> <p>Color Accuracy (CRI): >80 CRI</p> <p>R9 Value: High color performance with R9 greater than 0</p> <p>Color Consistency: <7-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color</p> <p>Color Stability: LED color temperature is warrantied to shift no more than 200K in color temperature over a 5-year period</p> <p>Color Uniformity: RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.</p>

Technical Specifications (continued)

Installation

Installation Method:

UL Type B, Ballast Bypass

Installation Orientation:

Universal Installation

Base Type:

GX24D

Construction

Shape:

PLT

Finish:

White

Endcap Material:

Copper

Enclosure Material:

Polycarbonate

Lens Finish:

Frosted

Compliance

Listings:

UL Classified, UL Recognized

Environment:

Suitable for use indoors in dry and damp environments.

Fixture Rating:

Suitable for use in enclosed fixtures.
Suitable for use in open fixtures.

Energy Star Approved:

No

DLC Listed:

This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements.

Certification Model Number:

T20104(PLT-15-O-8FA-BYP)

California Title 20 Compliant:

No

California Title 24 JA8 Compliant:

No

California Energy Commission (CEC) Status:

Not Lawful for Sales in California

NSF Listed:

Meets NSF/ANSI standards for use in Food Zone (non-contact), Splash, and Non-Food Zones. Tube guard required in open fixtures.

IESNA LM-79 & LM-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

RoHS:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15 of the FCC Rules

Other

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	9.13	7.09	7.32
PALLET	1	47.24	39.37	51.18

Dimension

