



Color: Bronze

Weight: 177.5 lbs

Project:	Type:
Prepared By:	Date:

**Technical Specifications**

**Compliance**

**CSA Listed:**

Suitable for wet locations

**Performance**

**Description:**

Steel pole 4" round 7 gauge 20 foot welded tenon square base

**Construction**

**Shaft:**

46,000 p.s.i. minimum yield.

**Hand Holes:**

Reinforced with grounding lug and removable cover

**Base Plates:**

36,000 p.s.i. minimum yield.

**Color:**

Bronze powder coating

**Height:**

20 ft

**Gauge:**

7

**Wall Thickness:**

3/16"

**Shaft Size:**

4"

**Anchor Bolt Templates:**

WARNING Template must be printed on 11" x 17" sheet for actual size. CHECK SCALE BEFORE USING. Templates shipped with anchor bolts and available [online](#).

**Max EPA's/Max Weights:**

- 70MPH 14.9 ft/410 lb.
- 80MPH 10.7 ft/350 lb.
- 90MPH 7.8 ft/165 lb.
- 100MPH 5.8 ft/130 lb.
- 110MPH 4.2 ft/70 lb.
- 120MPH 3.1 ft/60 lb.
- 130MPH 2.1 ft/50 lb.
- 140MPH 1.4 ft/50 lb.
- 150MPH 0.8ft./20 lb

**Accessories:**

Base/Cap: [BASE-R4](#)


Anchor Bolts: [BOLT4/7](#)

**Other**

**Terms of Sale:**

Pole Terms of Sale is available [online](#).

**Dimensions**



**Features**

- Designed for ground mounting
- Heavy duty TGIC polyester coating
- Reinforced hand holes with grounding lug and removable cover for easy wiring access
- Pole caps, base covers & bolts are sold separately
- Custom manufactured for each application

**Ordering Matrix**

Family	Shape	Size	Gauge	Height	Drilled/Welded Tenon
P	R	4	7	20	WT
	R = Round	4 = 4"	7 = 7	10 = 10'	D2 = Drilled
	TR = Tapered Round	5 = 5"	11 = 11	15 = 15'	WT = Welded Tenon
		6 = 6"		20 = 20'	
		7 = 7"		25 = 25'	
		8 = 8"		30 = 30'	