



Features

- Class 2 12W Constant voltage dimmable plug-in driver (15-100% control with most TRIAC dimmers)
- Features terminal block for easy wiring and in-line rocker switch on power cord for convenient On/Off control
- 6ft 18AWG power cord with 2-prong plug
- 6ft lead wire with attached terminal block
- cETLus Listed as a Recognized Component (dry locations)

Wattage/Voltage Options

- 12W (12V)

Listing / Ratings



PS Plug-in 12W Driver - 12V

This low profile dimmable plug-in driver has wire cover strain reliefs at both primary and secondary sides. It includes an attached terminal block to quickly connect low voltage lead wires. For dimming applications, a 4W minimum load must be met.

Technical Information

Series	PS Plug-in 12V
Max Load	12W
Minimum Load	3W (non-dimming); 4W (dimming)
Input Voltage	100-120V AC, 50/60Hz
Output Voltage	12V DC
Dimmable	15-100% (with TRIAC for most products)
Input Wire	6ft 18AWG power cord + 2-prong polarized plug
Output Wire	5ft 24AWG tail with 4-port terminal block
Rating	cETLus Recognized (dry locations)
Dimensions	5-1/4"L x 2"W x 11/16"H

Ordering Information

PS-12-12VPI-T	PS Plug-in 12V - 12W Driver
----------------------	-----------------------------