

WAC LIGHTING

Ion 2" Square

New Construction Downlight

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

| Model | Beam | Color Temp & CRI | Lumens | CBCP | Finish |
|--------|-------|------------------|--------|------|----------|
| R2DSDN | F 35° | 930 3000K - 90 | 755 | 1014 | WT White |

Example: **R2DSDN-F930-WT**

DESCRIPTION

Minimum profile downlight with metal conduit and driver included for easy remodel or new construction installation.

FEATURES

- Sold as new construction, may be configured in field for remodel
- Metal Conduit with Quick Connect to allow for easy installation
- Driver included
- 5 year warranty

SPECIFICATIONS

| | |
|---------------------------|---|
| Construction | Die-cast Aluminum with 20-gauge Cold Rolled Steel Driver Box |
| Power: | 9W |
| Input: | 120-277 VAC,50/60Hz |
| Dimming: | ELV: 100-10% , TRIAC: 100-5% |
| Light Source: | Integrated LED |
| Lens: | Frosted TIR lens |
| Rated Life: | 50,000 Hours |
| Mounting: | New construction housings included with hanger bars |
| Cut Out: | 3" |
| Finish: | Electrostatically Powder Coated: White |
| Ceiling Thickness: | 1/2" - 1 1/2" |
| Operating Temp: | -4°F to 104°F (-20°C to 40°C) |
| Standards: | ETL, cETL, Wet Location Listed, Energy Star 2.0, Title 24 JA8 Compliant, Airtight, IC |



FINISHES:



White