

# WAC LIGHTING

## Lotos R 4"

### Adjustable Downlight 5CCT

Fixture Type: \_\_\_\_\_  
Catalog Number: \_\_\_\_\_  
Project: \_\_\_\_\_  
Location: \_\_\_\_\_

Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
R4ERA2R	W 50	9CS 2700K/3000K/3500K/4000K/5000K - 90	740 775	733 750	BK Black WT White

Example: **R4ERA2R-W9CS-BK**

#### FEATURES


- 5-CCT Switchable between 2700K and 5000K
- Multiple LED array for uniform illumination
- Rotatable multi-axis gimbal ring
- Driver included
- 5 year warranty

#### SPECIFICATIONS

<b>Construction</b>	Steel with frosted TIR lens
<b>Power:</b>	9W
<b>Input:</b>	120 -277 VAC,50/60Hz
<b>Dimming:</b>	ELV: 100-5% , TRIAC: 100-5%
<b>Light Source:</b>	Integrated LED
<b>Lens:</b>	Translucent acrylic diffuser
<b>Rated Life:</b>	50,000 Hours
<b>Mounting:</b>	Heavy gauge retention clips secures fixture to ceiling
<b>Cut Out:</b>	4"
<b>Finish:</b>	Electrostatically powder coated White, Electrostatically powder coated Black
<b>Ceiling Thickness:</b>	1/2" - 1"
<b>Operating Temp:</b>	-4°F to 104°F (-20°C to 40°C)
<b>Standards:</b>	ETL, cETL, Wet Location Listed, Title 24 JA8 Compliant, Airtight, IC



#### FINISHES:




# WAC LIGHTING

## Lotos R 4"

Adjustable Downlight 5CCT

Fixture Type: \_\_\_\_\_  
Catalog Number: \_\_\_\_\_  
Project: \_\_\_\_\_  
Location: \_\_\_\_\_

### ACCESSORIES

	<i>Model</i>	<i>Description</i>	<i>Finish</i>
	RER-FRAME	Lotos	