



|              |       |
|--------------|-------|
| Project:     | Type: |
| Prepared By: | Date: |

| Driver Info |                  | LED Info       |                           |
|-------------|------------------|----------------|---------------------------|
| Type        | Constant Current | Watts          | 11W                       |
| 120V        | 0.09A            | Color Temp     | 2700/3000/3500/4000/5000K |
| 208V        | N/A              | Color Accuracy | 92 CRI                    |
| 240V        | N/A              | L70 Lifespan   | 50,000 Hours              |
| 277V        | N/A              | Lumens         | 900 lm                    |
| Input Watts | 11W              | Efficacy       | 82                        |

Technical Specifications

Performance

Product Type:  
Recessed Retrofit

Description:  
Contractor-grade retrofit downlights offered with up to 5 field selectable color temperatures in 1 model.

Wattage Equivalency:  
65W Incandescent

Input Wattage:  
11W

Lumens:  
2700K @ 938lm; 3000K @ 952lm; 3500K @ 968lm;  
4000K @ 981lm; 5000K @ 1,050lm

Efficacy:  
2700K @ 96lm/W; 3000K @ 100lm/W; 3500K @ 103lm/W; 4000K @ 102lm/W; 5000K @ 105lm/W

L70 Lifespan:  
50,000-Hour LED lifespan based on IES LM-70 results

Electrical

Driver:  
Constant Current, 60 Hz, 120V, 120V: 0.09 A

THD:  
≤20%

Power Factor:  
≥0.9

Dimmable:  
Yes, dims down to 10% on compatible TRIAC/ELV system.  
See Dimmer Compatibility List.

Input Voltage:  
120V

Operating Frequency:  
60 Hz

Input Current @ 120V (mA):  
90mA

Operating Temperature:  
-22°F to 104°F (-30°C to 40°C)

LED Characteristics

Color Temperature:  
Field adjustable via dip switch  
2700/3000/3500/4000/5000K

Color Accuracy (CRI):  
>90 CRI

R9 Value:  
High color performance with R9 greater than or equal to 50

Color Consistency:  
<4-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

Color Stability:  
LED color temperature is warrantied to shift no more than 200K in color temperature over a 5-year period

Color Uniformity:  
RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

Installation

Mounting:  
Recessed Housing

Construction

Size:  
6"

Shape:  
Round

**Technical Specifications (continued)****Finish:**

White

**Enclosure Material:**

Metal

**Trim Style:**

Baffle

**Lens:**

Polycarbonate light diffuser distributes light evenly and smoothly for general lighting applications

**Cut Out Template Size:**

6 5/16"

**Compliance****Listings:**

UL Recognized, UL Classified

**Environment:**

Suitable for use in dry, damp, and wet environments.

**IC Rated:**

No

**Air Tight:**

No

**DLC Listed:**

No

**T20 Compliant:**

Can be used to conform with the requirements of California Title 20

**California Title 24 JA8 Compliant:**

Can be used to conform with the requirements of California Title 24 Part 6

**California Energy Commission (CEC) Status:**

Lawful for Sales in California

**NEC Compliant:**

Suitable for use in closets. Compliant with NEC Sec. 410.16 (A)(1) and 410.16 (C3).

**IESNA LM-79 & LM-80 Testing:**

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

**RoHS:**

Mercury and UV free. RoHS-compliant components.

**FCC:**

Complies with Part 15B of the FCC Rules

**Energy Star Approved:**

ENERGY STAR® Version 1.0 Certified

**Certification Model Number:**

DLR0006(R6R8830120WB)

**Other****Accessories:**[RFLED-RETROBAND](#)

Retrofit Band

[RFLED-GOOF-6R-8R-W](#)

6"-8" Goof Ring

[DLTRIM/R6RB-BN](#)

6" Round Baffle Brushed Nickel Color Trim

[DLTRIM/R6Rb-BRZ](#)

6" Round Baffle Bronze Color Trim

[DLTRIM/R6RB-B](#)

6" Round Baffle Black Color Trim

[DRI-25-EMGR-DC](#)

Battery Backup Driver

[DRI-21-EMGR-DC-D10](#)

Battery Backup Driver T20


**Warranty:**

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).


Case and Pallet Dimensions

|        | QTY | LENGTH (in) | WIDTH (in) | HEIGHT (in) |
|--------|-----|-------------|------------|-------------|
| CASE   | 4   | 15.47       | 7.99       | 8           |
| PALLET | 600 | 7.56        | 3.82       | 82.28       |

Dimension



Light Distribution



Features

- Use to replace traditional halogen and incandescent light sources
- Durable metal construction: dent and scratch resistant
- 5 Color temperature selectable 2700K, 3000K, 3500K, 4000K, & 5000K
- Compatible with most standard recessed housings
- Color trims sold separately

Ordering Matrix

| Family | Size   | Shape     | Wattage  | CRI/Color Temp               | Driver     | Finish    | Trim       |
|--------|--------|-----------|----------|------------------------------|------------|-----------|------------|
| R      | 6      | R         | 11       | 9FA                          | 120        | W         | B          |
|        | 4 = 4" | R = Round | 8 = 8W   | 9FA = 90 CRI, CCT Adjustable | 120 = 120V | W = White | B = Baffle |
|        | 6 = 6" |           | 10 = 10W |                              |            |           | S = Smooth |
|        |        |           | 11 = 11W |                              |            |           |            |
|        |        |           | 14 = 14W |                              |            |           |            |