

Project:	Type:	Prepared By:	Date:
-----------------	--------------	---------------------	--------------



Features and Benefits

- Motion detection
- 360° detection through walls and objects
- Continuous detection pattern
- On-off functionality
- Standby level options: off, 20% dim, 40% dim, or 60% dim
- Hold time options for motion detection: 30 seconds, 90 seconds, 5 minutes, or 10 minutes
- If no motion is detected: lamp will be switched to 0-60% brightness
- If any motion is detected: lamp returns to 100% output to pre-defined hold time

Technical Specifications		Other
<p>Performance</p> <p>Product Type: PIR Sensor</p> <p>L70 Lifespan: 50,000 Hours</p> <hr/> <p>Electrical</p> <p>Input Voltage: 15VDC</p> <p>Max Input Current: 0.1A</p> <p>Max Output Current: 0.02A</p> <p>Detection Angle: 120 degrees</p> <p>Max Mounting Height: 19.7 ft</p> <p>Detection Radius: 13.12 ft</p>	<p>Standby Dim Levels: 0/20%/40%/60%</p> <p>Input Frequency: 5.8 GHz +/- 75MHz</p> <p>Output Voltage: 10VDC</p> <p>Operating Frequency: 5.8GHz</p> <p>Operating Current: 20mA</p> <p>Transmit Power: 1mW</p> <hr/> <p>Compliance</p> <p>California Energy Commission (CEC) Status: Lawful for Sales in California</p>	<p>Warranty: RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.</p>

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	100	9.8	9.8	9
PALLET	10000	49.2	40	47.3

Dimension

