



Color: White

Weight: 14.9 lbs

<b>Project:</b>	<b>Type:</b>
<b>Prepared By:</b>	<b>Date:</b>

Driver Info		LED Info	
Type	Constant Current	Watts	29W
120V	0.25A	Color Temp	Field Adjustable
208V	0.15A	Color Accuracy	83-85 CRI
240V	0.13A	L70 Lifespan	100,000 Hours
277V	0.12A	Lumens	2,916-5,668 lm
Input Watts	18.2-36.4W	Efficacy	145.4-166 lm/W

## Technical Specifications

### Field Adjustability

#### Field Adjustable:

Field Adjustable Light Output:

1' x 4': 39W/29W/19W (factory default 29W)

Color temperature selectable by 3500K, 4000K and 5000K (factory default 4000K)

### Compliance

#### UL Listed:

Suitable for damp locations

#### IESNA LM-79 & LM-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

#### Trade Agreements Act Compliant:

This product is a product of Cambodia and a "designated country" end product that complies with the Trade Agreements Act

### Electrical

#### Driver:

Class 2, Constant Current, 120-277V, 50/60 Hz, 120V: 0.25A, 208V: 0.14A, 240V: 0.12A, 277V: 0.11A

#### THD:

11.9% at 120V, 7.84% at 277V

#### Power Factor:

99.2% at 120V, 96.4% at 277V

#### Surge Protection:

2 kV

### Construction

#### Cold Weather Starting:

The minimum starting temperature is -22°F (-30°C)

#### Ambient Temperature:

Suitable for use in up to 104°F (40°C)

#### IC Rated:

Suitable for direct contact with insulation

#### Housing:

Die-formed, 20-gauge, cold-rolled steel

#### Reflector:

Integral reflector (on the sides) with high reflectance finish, optimized for uniform distribution.

#### Lens:

Frosted polycarbonate lens

#### Finish:

Formulated for high durability and long-lasting color

#### Green Technology:

Mercury and UV free. RoHS-compliant components.

### Installation

#### Mounting:

Recessed ceiling

### LED Characteristics

#### LEDs:

Long-life, high-efficacy, surface-mount LEDs

#### Color Stability:

LED color temperature is warrantied to shift no more than 200K in color temperature over a 5-year period

#### Color Uniformity:

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

### Performance

#### Lifespan:

100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations


## Technical Specifications (continued)

### Other

#### 5-Year, No-Compromise Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

## Dimensions



## Ordering Matrix

Family	Size/Wattage	Color Temp	Driver	Options	Battery Backup
SWISHFA	1X4		/D10		
	<b>2X2</b> = 2' x 2', 39/29/19W <b>1X4</b> = 1' x 4', 39/29/19W <b>2X4</b> = 2' x 4', 49/39/29W	<b>Blank</b> = 3500/4000/5000K CCT Adjustable	<b>/D10</b> = 0-10V Dimming	<b>Blank</b> = No Option <b>/MVS</b> = Microwave Occupancy Sensor <b>/LC</b> = Lightcloud	<b>Blank</b> = No Option <b>/E2</b> = Battery Backup