

Project Name

Location

Prepared By



SATCO S11972

13T8U6/LED/22.5-840/DUAL

Notes

[www] 05-07-2023 09:43:04

General	
Status	Discontinued
Substitute	S18413
Watts	13W
Incandescent Equivalent	50W
Fluorescent Equivalent	32W
Volts	120V-277V
Ballast Type	Type A/B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	22.5
Finish	Frost
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80+
Lumens	2000L
Beam Spread	160
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	U-Bend
Technology	LED

Electrical	
Ballasting Requirements	Ballast required (Type A) or Ballast Bypass (Type B)
Operating Frequency	50/60Hz
Dimming Note	Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
Power Factor	0.9
THD	20%
Operating Temperature	-25C (-13F) to +45C (+113F)

Physical	
MOL	22.59
MOD	1.1
Leg Spacing	6
Material	Plastic
Lens Finish	Frost
Lens Material	Plastic (PS)
Housing Color	White
Weight (lb.)	0.5

Additional Information	
Shatter-Proof Type	Yes
Tube Guard Use	Yes
Installation Notes	Not for use in vapor tight fixtures. Direct replacement for 32W/23T8/U6 lamps only
Rated For Enclosed Fixture	Yes
Warranty	5-Years

Compliance	
Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Damp
DLC Approved	Yes
DLC ID	PLX80LFIAOD6
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	ETL Sanitation listed (conforms to NSF)
SDS Sheet	LED_Lamp