

Project Name

Location

Prepared By



## SATCO S13190

40W/LED/HID/ED28/850/EX39/WH

**Notes**

(www) 05-07-2023 09:42:04

**General**

Status	Active
Watts	40W
HID Equivalent	175W
Volts	120V-277V
Shape	ED28
Base	Mogul Extended
ANSI Base	EX39
Finish	White
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80+
Lumens	6000L
Beam Spread	320
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	LED HID
Technology	LED
Min Compartment Size	Length: 9.25 in. Width: 9.25 in. Height: 17.28 in.
Ballasting Requirements	Ballast Bypass

**Electrical**

Operating Frequency	60Hz
Power Factor	0.9
Operating Position	Universal
Surge Protection	Built-in surge protection - 4KV
THD	<20%
Operating Temperature	-30C (-22F) to +65C (+149F)

**Physical**

MOL	8.4
MOD	3.54
Housing Color	None
Weight (lb.)	0.46

**Additional Information**

Rated For Enclosed Fixture	Yes
IP Rating	IP65
Installation Notes	Not for use in vapor tight fixtures.
Warranty	5-Years

**Compliance**

Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Wet
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp