



Type IC, Wet, Air-Tight & Open Plenum

DESCRIPTION


5" Round 30° Sloped Deep Regressed LED
Commercial Grade Quality Built To Last

FEATURES & BENEFITS

30° Sloped - perfect for 30° sloped ceilings and wall washing
5 single CCT + Dim to Warm + 5CCT field selectable options
Type IC, Air-Tight & Wet - No Housing Required
3 1/2" Deep - Install Where Ceiling Space Is Limited
Armored Cable & Metal Connectors - Open Plenum Rated
Driver Inside Connection Box with Romex Quick Connectors
and Knock Outs - Fast Installation & No Junction Box Needed

DIMENSIONS ID 4 1/4" OD 6 1/4"

Ceiling Clearance Required: 3 1/4"
CUT OUT 5" to 5 1/2"



120V TRIAC Dimmable Driver Included

Optional 120V-347V
0-10V Dimmable
Order Separately as
[model # LLL-LD2050TR](#)



ORDERING GUIDE Example **LD4R-30K-HO-5R-SL30-WH**

	CCT		Reflector - Trim	Beam Angle	
LD4R	- xxK	-HO	- 5R-SL30-WH		
2700K	27K		- 5R-SL30-BK	blank for 30°	
3000K	30K		- 5R-SL30-ORB	-15D	15°
3500K	35K			-60D	60°
4000K	40K				
5000K	50K				
DTW 30-20K	32K		Dim To Warm 3000K to 2000K		
DTW 30-18K	3018K		Dim To Warm 3000K to 1800K		
5CCT	5CCT		User selectable 27-30-35-40-50K		



Lotus LED Lights USA

250 H Street # 301, Blaine WA 98230 tel 360-200-5500
Hainesport NJ, Naples FL, Vancouver WA

www.LotusLEDLights.com

mailing addresses
warehouses

LD4R-HO-5R-SL30

5" Round 30° Sloped Regressed LED Plenum Rated 18W

Project:

Location:

Model #:

Qty:

Notes:

SPECIFICATION	
Applications	Recessed Sloped Ceilings and Wall Washing
Power	18W
Color Temperature CCT (K)	2700 3000 3500 4000 5000 DTW 30-20K DTW 30-18K
Light Output Single CCT (lm)	1520 1610 1550 1690 1630 1310 1500
Light Output 5CCT (lm)	1320 1400 1520 1590 1600
Beam Angle	30° (default), 15° & 60° optional
Slope Angle	30°
CRI	90 +
Default Driver Input	120V AC Triac Dimmable
Optional Driver Input	120V-347V AC 0-10V Dimmable
Junction Box Wire Capacity	Max 5 No 12 AWG or 8 No 14 AWG
Approved Location	Insulated Ceilings, Open Plenum, Wet Locations
IP Rating	IP 54
Air Tight	Yes
Ambient Temperature	-40°F (-40°C) to +104°F (+40°C)
Projected Life	70% Light Output at 50,000 Hours
Certification	cULus
Warranty	10 Year Residential / 5 Year Commercial

AVAILABLE TRIMS



5R-SL30-WH
White



5R-SL30-BK
Black



5R-SL30-ORB
Oil Rubbed Bronze

ACCESSORIES

Sold Separately



[Armored Low Voltage Extension 10ft model MEC10](#)



[26" Long Flat Plate 5" Hole model # RIP5](#)



[5" Hole Flanged with Hanger Bars model # FRP5](#)

COMPLIANCE



Type IC & Air-Tight
Wet Location
Open Plenum

Lotus LED Lights USA

250 H Street # 301, Blaine WA 98230 tel 360-200-5500
Hainesport NJ, Naples FL, Vancouver WA

www.LotusLEDLights.com

mailing addresses
warehouses

Lotus LED Lights CANADA

1080 Cliveden Ave # 6, Delta BC V3M 6G6 tel 604-538-3090
Delta BC & Mississauga ON