

Project:	Type:	Prepared By:	Date:
-----------------	--------------	---------------------	--------------



Features and Benefits

- Replacement for conventional fluorescent T8 and T12 linear tubes
- Integral Driver enables lamp to be wired directly to line voltage without need for an external driver or ballast
- Double ended wiring method
- Works with shunted sockets.
- Approximately 50% more energy efficient when compared to Fluorescent T8 lamps
- 50,000 hour Lifespan.
- Rated for use in enclosed and open fixtures in dry or damp locations
- Diffused frosted lens will maintain the same light quality over time
- Instant on full brightness
- Environmentally friendly, no mercury used
- NSF Listed: NSF/ANSI Standard 2 - Food Equipment - Splash Zone (Not for Direct Food Zone without additional fixture considerations)
- Internal thermal fuse for added safety
- Emergency back up available

Technical Specifications		
Performance	Nominal Length:	Installation Type:
Product Type: Linear	4 ft	Type B, Double Ended wiring
Input Wattage: 10.5W	Finish: Frosted	Electrical
Lumens: 1,700lm	For Use Outdoors in Open Fixtures: No	THD: <20%
Efficacy: 160lm/W	LED Characteristics	Power Factor: >0.9
L70 Lifespan: 50,000 Hours	Color Temperature: 3500K Neutral White	Operating Temperature: -20°C to 45°C (-4°F to 113°F)
Wattage Equivalency: 25W/28W/30W/32W Fluorescent	Color Accuracy (CRI): 82 CRI	Dimming: No
Construction	Beam Angle: 210°	Input Voltage: 120-277V AC
Material: Glass	Installation	Operating Frequency: 50/60Hz
Bulb Shape: T8	Base Type: G13	Input Current @ 120V: 106mA
		Input Current @ 277V: 44mA

Technical Specifications (continued)

Other

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Compliance

UL Recognized:

Yes

UL Classified:

Yes

NSF Listed:

Meets NSF/ANSI standards for use in Food Zone (non-contact), Splash, and Non-Food Zones. Tube guard required in open fixtures.

Certification Model Number:

T10043

California Energy Commission (CEC) Status:

Lawful for Sales in California

Application:

Suitable for damp locations and totally enclosed fixtures.

DLC Listed:

This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements.

DLC Product Code: PD2KJ0EC

Minimum Compartment Size




Length x Width x Height [in]	Lamp Quantity
48	4

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	25	48.8	5.9	6
PALLET	1200	47.2	40	51.3

Wiring Diagram

Dimension



Light Distribution

