



Weight: 3.7 lbs

Project:	Type:
Prepared By:	Date:

Driver Info		LED Info	
Type	N/A	Watts	N/A
120V	N/A	Color Temp	N/A
208V	N/A	Color Accuracy	N/A
240V	N/A	L70 Lifespan	N/A
277V	N/A	Lumens	N/A
Input Watts	N/A	Efficacy	N/A

Technical Specifications

Performance

Description:

Versatile driver with high-performance dimming on ELV, TRIAC, and 0-10V dimming system that allows for dim-to-dark

L70 Lifespan:

50,000-Hour LED lifespan based on IES LM-70 results

Electrical

Driver:

Constant Voltage, Class 2

THD:

<20%

Power Factor:

>0.95

Dimmable:

Yes, dimmable down to 0.1% on compatible TRIAC/ELV or 0-10V dimming systems. See Dimmer Compatibility List.

Input Voltage:

100-277V

Output Power:

96W Max

Output Voltage:

24VDC

Output Current:

8A total / 4x2A

Operating Frequency:

47-63Hz

Input Current @ 100V (mA):

1.2A/CHN

Operating Temperature:

-20°C to 45°C (-4°F to 113°F)

Storage Temperature:

-4°F (-20°C) to 140°F(60°C)

Flicker:

No flicker

Installation

Mounting:

Screws fix

Compliance

Listings:

UL8750

Environment:

Suitable for use indoors and outdoors in dry, damp, or wet environments.

IP Rating:

IP65

Air Tight:

Yes

Certification Model Number:

TOD-96X2

California Title 20 Compliant:

No

California Title 24 JA8 Compliant:

No

California Energy Commission (CEC) Status:

Lawful for Sales in California

FCC:

Complies with Part 15 of the FCC Rules

Technical Specifications (continued)

Other

Compatible Products:

Compatible with the following ARCTAPE products:

TICYY, TICY, TICYN, TICN, TICCW, TICLYY, TICLY,
TICLYN, TICLN, TICLCW, TICHYY, TICHY, TICHYN,
TICHN, TICHCW

Compatible with the following FLEXTAPE products:

TOSYY, TOSY, TOSYN, TOSN, TOSCW, TOSLYY, TOSLY,
TOSLYN, TOSLN, TOSLCW, TOSHYY, TOSHY, TOSHYN,
TOSHN, TOSHCW

Compatible with the following NEOFLEX products:

TNIFY, TNFY, TNFYN, TNFN, TNFLGY

Compatible with the following NEOFLEX products:

TOCYY, TOCY, TOCYN, TOCN, TOCCW