



Color: Bronze

Weight: 6.0 lbs

<b>Project:</b>	<b>Type:</b>
<b>Prepared By:</b>	<b>Date:</b>

Driver Info		LED Info	
Type	Constant Current	Watts	60/50/40W
120V	0.51A/0.41A/0.33A	Color Temp	3000/4000/5000K
208V	0.30A/0.24A/0.20A	Color Accuracy	83-85 CRI
240V	0.27A/0.21A/0.18A	L70 Lifespan	N/A
277V	0.23A/0.19A/0.16A	Lumens	5,929-9,145 lm
Input Watts	38.6-61.1W	Efficacy	141.5-162.4 lm/W

**Technical Specifications**

**Field Adjustability**

**Field Adjustable:**

Field Adjustable Light Output:  
60W/50W/40W (factory default: 60W)  
Color Temperature Selectable:  
3000K, 4000K and 5000K (factory default:4000K)  
Photocell Selectable:  
Built-in on/off photocell (factory default: off)

**Compliance**

**UL Listed:**

Suitable for wet locations

**IESNA LM-79 & LM-80 Testing:**

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

**IP Rating:**

Ingress protection rating of IP65 for dust and water

**Trade Agreements Act Compliant:**

This product is a product of Cambodia and a "designated country" end product that complies with the Trade Agreements Act

**DLC Listed:**

This product is listed by Design Lights Consortium (DLC) as an ultra-efficient premium product that qualifies for the highest tier of rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements.  
DLC Product Code: S-3B2XNC (Stairwell and Passageway Luminaires)  
DLC Product Code: S-Q4BNSD (Fuel Pump Canopy Luminaires)

**Electrical**

**Driver:**

Constant Current, Class 1, 120-277V, 50/60 Hz:  
60W: 120V: 0.51A, 208V: 0.30A, 240V: 0.27A, 277V: 0.23A  
50W: 120V: 0.41A, 208V: 0.24A, 240V: 0.21A, 277V: 0.19A  
40W: 120V: 0.33A, 208V: 0.20A, 240V: 0.18A, 277V: 0.16A

**Dimming Driver:**

Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims down to 10%.

**Aux Power Supply:**

Yes

**Dim to Off:**

Yes

**Surge Protection:**

L/N: 4KV, L/N-PE: 6KV

**Photocell:**

Built-in photocell included with on/off switch

**LED Characteristics**

**LEDs:**

Long-life, high-efficacy, surface-mount LEDs

**Color Uniformity:**

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

**Performance**

**Lifespan:**

100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

**Construction**

**Cold Weather Starting:**

The minimum starting temperature is -40°C (-40°F)

**Maximum Ambient Temperature:**

Suitable for use in up to 40°C (104°F)

**Lens:**

Polycarbonate clear flat lens

**Gaskets:**

Ethylene Propylene Diene Monomer (EPDM)



**Technical Specifications (continued)**

**Housing:**

Die-cast aluminum

**Reflector/Tray:**

Aluminum

**Finish:**

Formulated for high durability and long-lasting color

**Green Technology:**


Mercury and UV free. RoHS-compliant components.

**Other**

**5-Year Limited Warranty:**

The RAB 5-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

**Dimensions**



**Features**

- 100,000-Hour LED lifespan
- 0-10V Dimming
- IP65 Rated
- 5-Year, limited warranty

**Ordering Matrix**

Family	Wattage	Color Temp	Lens	Finish	Driver	Controls	Battery Backup
VAN34	60		F				
	30 = 30/20/10W 90 = 90/80/70W 60 = 60/50/40W	Blank = 3000/4000/5000K CCT Adjustable	F = Flat Lens FFR = Frosted Flat Lens FR = Frosted Drop Lens Blank = Drop Lens	W = White Blank = Bronze	Blank = 120-277V, 0-10V Dimming /480 = 480V, 0-10V Dimming	/MVS = Microwave Sensor /LCBS/MVS = Lightcloud Blue w/MVS Sensor /LC = Lightcloud Blank = On/Off Photocell	Blank = None /E = Battery Backup