



5"/6" LED Recessed Downlight

10.5 Watts 670 Lumens



The ETi 5"/6" LED Recessed Downlight produces 670 lumens of high quality, bright white light (2700K CCT) and offers traic dimming.

This commercial-grade LED Recessed Downlight is ideal for retrofiting inefficient fixture in malls, hospitals, airports, offices, lobbies and other applications. Energy Star certified, it uses only 10.5 watts of power and is designed for long life – 45.6 years or 50,000 hours of continuous use.

The design is also versatile and easy to install — the wiring can be connected within its own junction box or to an existing recessed can fixture cUL us classified for use in damp locations and IC rated for direct contact with insulation. Warranty 5 years.

KEY FEATURES & BENEFITS

- 10.5 Watts — Low Power and High Performance
- 670 lumens
- 120V
- CRI 90
- Traic Dimming
- 2700k CCT (also 4000K available)
- cUL Classified for Damp Locations and IC Rated for direct contact with insulation
- Rated life: 50,000 hours

FIXTURE DIMENSIONS



Diameter= 7.5"
Height = 3.3"
Fits 5"/6" openings

Weight = 0.79 lbs



This light source meets restrictions on hazardous substances.

APPLICATION INFORMATION

This commercial-grade LED Recessed Downlight is ideal for retrofitting inefficient fixtures in hotels, malls, hospitals, airports, offices, lobbies and other commercial applications.

855 -384 -7754 www.etissl.com

5"/6" LED Recessed Downlight

10.5 Watts, 670 Lumens

SPECIFICATION DATA

Project _____
 Item Number _____
 Prepared by _____
 Date _____



ORDERING INFORMATION

Item Number	Description	Wattage	Input Voltage (VAC)	Average Rated Life ¹	Typical Lumens ²	CCT ³	CRI ⁴	Power Factor	R9	Duv	CBCP	Beam	Operating Frequency
53167103	5"/6" Recessed Downlight	10.5	120V	50,000	670	2700K	90	>.9	46	-0.0012	298	103	60Hz
¹ Hours lifetime with 70% lumen maintenance													
² Thermally stable typical lumens (± 10%)													
³ Thermally stable CCT (± 10%)													
⁴ Color rendering index/Ra													

SHIPPING INFORMATION

Item Number	Item UPC	Item Dimensions (in packaging) H x L x W	Item Weight (lbs)	Inner Pack Qty	Inner Carton Bar Code	Inner Carton Dimensions H x L x W	Inner Pack Weight (lbs)	Master Pack Qty	Master Carton Bar Code	Master Dimensions H x L x W	Master Pack Weight (lbs)
53167103	8494 8900 3023	8.86" x3.66" x8.86"	0.79	N/A	N/A	N/A	N/A	4	508494 8900 3028	9.45" x8.43" x19.06"	6.31

LED lighting facts[®]
Prepared in U.S.A.

Light Output (Lumens) 670
 Watts 10.5
 Lumens per Watt (Efficacy) 63.81

Color Accuracy
 Color Rendering Index (CRI) 90

Light Color
 Correlated Color Temperature (CCT) 2700 (Warm White)

2700K 3000K 4500K 6500K

All results are according to IESNA LM 79-2008. Approved Authority for the Electrical and Photometric Testing of Solid State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit www.lightingfacts.com for the Label Reference Guide.

Registration Number: YN84-C210Y
 Model Number: 53167103X000-00
 Type Luminaire: Downlight

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, please see www.etissl.com/fcc15b

ETi Solid State Lighting, Inc., 720 Corporate Woods Parkway, Vernon Hills, IL 60061
 855-384-7754 www.etissl.com