



## Features

- Constant voltage non-dimming plug-in driver
- Available in 12V and 24V options
- Wattages ranging from 40W up to 96W
- 6ft 18AWG power cord with 3-prong plug
- 5ft 18AWG tail with male DC jack
- cULus Listed (dry locations)

## Wattage/Voltage Options

- 40W (12V DC | 24V DC)
- 60W (24V DC)
- 90W (24V DC)
- 96W (12V DC)

### 2-wire DC Adapter Accessory (DC-VPI)



### 2-wire DC Adapter Accessory (DC-HW)



## Listing / Ratings



## PS Plug-in Series

Use one of these five constant voltage DC power supplies for non-dimming plug-in applications, based on the capacity and voltage needed. The DC-HW accessory can be used with Trulux tape light, ideally with a switched outlet since the driver does not include an inline switch. Use the DC-VPI for powering low voltage products with bare leads, such as LightStar reels. cULus Listed for use in dry locations.

## Technical Information

Series	PS Plug-in 12V/24V
Max Load	See ordering information
Minimum Load	N/A
Input Voltage	120V AC
Output Voltage	12V DC/24V DC
Dimmable	N/A
Input Wire	6ft 18AWG power cord + 3-prong plug
Output Wire	5ft 18AWG tail with male DC jack
Rating	cULus Listed (dry locations)
Dimensions	5-3/4"L x 2"W x 1-1/4"H (40W) 6-3/4"L x 2-3/8"W x 1-1/4"H (90W/96W)

## Ordering Information

<b>PS-40-12VPI</b>	PS Plug-in 12V DC - 40W Driver
<b>PS-96-12VPI</b>	PS Plug-in 12V DC - 96W Driver
<b>PS-40-24VPI</b>	PS Plug-in 24V DC - 40W Driver
<b>PS-60-24VPI</b>	PS Plug-in 24V DC - 60W Driver
<b>PS-90-24VPI</b>	PS Plug-in 24V DC - 90W Driver
<b>DC-VPI</b>	2-wire DC adapter cable - Bare wire to Female DC
<b>DC-HW</b>	2-wire DC adapter cable - Bare wire to Male DC